

SAFETY DATA SHEET

DATA SHEET Satin-Sheen

1 PRODUCT IDENTIFICATION AND COMPANY NAME

| Product Name | : F4 Paints Satin-Sheen | |
|------------------------|--|--------------------------|
| Product Identification | : Emulsion Based Sheen paint | |
| Supplier/Manufacturer | : F4 Paints | |
| Address | : NORTHLANDS MINI UNITS 7, NORTHLANDS BUSINESS PARK NEW MARKET ROAD, NORTHRIDING GAUTENG, SOUTH AFRICA | Cell phone: +27102205521 |

| 2 COMPOSITION/INFORMATION ON INGREDIENTS | | |
|--|--|--|
| Resin Base Hazardous Cor | Acrylic resin emulsion Acrylic resin and small amounts of organic solvents-this product is not classed as hazardous but should carry the following S Phrases S2, S24/25 | |
| 3 HAZARDS | IDENTIFICATION | |
| Physical/Chem Human Health | | |
| Environmental | Skin : In General no irritation | |
| 4 FIRST AID MEASURES | | |
| General | : In all cases of doubt, or when symptoms persist, seek medical attention. Never | |
| Inhalation | give anything by mouth to an unconscious person. Move to a safe area with fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice. | |
| Eye Contact Ingestion | Rinse thoroughly with water for at least 10 minutes. Seek medical attention. Do not induce vomiting. Keep person warm and at rest. Seek medical advice immediately and show the container or label. | |
| Skin Contact | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use a recognized skin cleanser. Do not use solvents or thinners. | |

5 FIRE-FIGHTING MEASURES

This paint is NOT flammable but the dry residue is combustible Expect no direct explosion hazard Use CO2, dry powder or foam

| 6 ACCIDENTAL RELEASE MEASURES | | |
|-------------------------------|--|--|
| Personal Precautions | : Ventilate the area. Avoid breathing in vapours. Remove all sources of ignition e.g. flames, sparks, static electricity and heat. | |
| Spill | : Contain and collect spillage with absorbent material. Dispose of according to local regulations. Do not allow spillage to enter sewerage drains or watercourses. | |



SAFETY DATA SHEET

DATA SHEET Satin-Sheen

| | DATA SHEET Satin-Sheen |
|--|---|
| 7 HANDLING AN | ID STORAGE |
| Handling : Storage : | Keep container tightly closed. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. After handling the material, workers should wash hands and face before eating, drinking and smoking. Always comply with health and safety regulations. Store in original container. Observe label precautions. Store in a cool, well- ventilated area away from incompatible materials and ignition sources. Keep away from oxidizing agents, strong alkaline and acids. No smoking. Containers which have been opened must be carefully resealed and kept upright to prevent leakage. |
| 8 EXPOSURE CO | ONTROL/PERSONAL PROTECTION |
| Engineering Measu | : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn. |
| Personal Protective Respiration | |
| Eyes Ingestion | Never tough eyes with dirty hands or gloves. : Observe the rules of hygiene. Wash hands and face before eating, |
| <i>Skin</i> Environmental Exp | drinking or smoking. : Use protective gloves. Wash in case of contact. osure Control : Do not allow product to enter sewerage drains or watercourses. |
| 9 PHYSICAL AN | D CHEMICAL PROPERTIES |
| Appearance Flash Point (ºC) Dilution/Wash up | : Opaque Liquid : Not flammable : Water |
| 10 STABLILTY AN | ND REACTIVITY |
| Stability Conditions to Avoid Materials to Avoid | Stable under recommended storage and handling conditions. Excessive heat – store below 30 degrees Celsius Oxidizing agents, strong alkaline or acidic materials. |
| 11 TOXICOLOGIC | AL INFORMATION |
| Prolonged inhalati | onged skin co <mark>ntact</mark> may cause irritation and skin inflammation. on of vapours in high concentrations may lead to headache, giddiness and nausea. with the product, irritation of the skin/mucous membranes. |
| 12 ECOLOGICAL | INFORMATION |
| | vailable on the preparation itself. ared a water pollutant. Do not allow to enter drains or watercourses. |
| 13 DISPOSAL CO | NSIDERATIONS |
| Dispose according | ter drains or watercourses. Ito state and local applicable regulations. are suitable for recycling. |
| 14 TRANSPORT I | NFORMATION |
| Not classified as dange | erous for transport. |



SAFETY DATA SHEET

DATA SHEET Satin-Sheen

15 REGULATORY INFORMATION

Classification: Not classified as hazardous

| S2: | Keep out of reach of Children |
|---------|----------------------------------|
| S24/25: | Avoid contact with eyes and skin |

16 OTHER INFORMATION

| Date of Printing Date if Issue Version | October 2022 October 2022 1 |
|--|---|
| Version Notice | The information in this SDS is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the product's properties. |
| | |