



# Contractor's First Coat/Primer

TECHNICAL DATA SHEET  
November 2022

<b>Product Description</b>	F4 Paints Contractor's First Coat/Primer is a new generation good opacity cost but property Effective matt Paint for interior/Exterior Ceiling and Wall areas	
<b>Application Areas</b>	<ul style="list-style-type: none"> <li>Dry Sound Cement Plaster or Fibre Cement</li> </ul>	
<b>Product Features</b>	<ul style="list-style-type: none"> <li>Good 2 Coat Opacity</li> <li>Good adhesion</li> <li>Excellent, no mess application properties.</li> <li>Quick drying 2 coats can be applied in one day.</li> <li>If correctly applied to a properly prepared substrate, the product has a life expectancy of 2Years, possibly longer.</li> </ul>	
<b>Product Data</b>	<b>Resin Base</b>	Acrylic resin emulsion
	<b>Drying Time</b>	Touch dry: ± 1 hour Hard dry: ± 2-3 hours
	<b>Film Thickness</b>	30-40 microns per coat
	<b>Spreading Rate</b>	4-6 SQM per 1 litre Although the spreading rate will vary with porosity and type of substrate, for uncoated new surfaces work on 3-5 square meters per litre for the first coat.
<b>Application Details</b>		
• <b>Mixing</b>	Always stir well before use with a flat paddle.	
• <b>Application Method</b>	<ul style="list-style-type: none"> <li>Brush, Roller</li> </ul>	
• <b>Thinning</b>	This Product is ready for use un-thinned; thinning with water will reduce its hiding power.	
• <b>Cleaning</b>	Application equipment clean up is with clean tap water.	
• <b>Application</b>	<ul style="list-style-type: none"> <li>Stir well before use.</li> <li>With brush or roller apply a generous coat of this Product to the area that needs protecting.</li> <li>Allow to dry 2-3 hours before recoating.</li> <li>With a Brush or roller apply a second generous coat.</li> <li>2 Coats of the Product are used for best results.</li> <li>This Product is ready for use un-thinned; thinning with water will reduce its hiding power.</li> <li>Clean tools immediately after use with clean tap water.</li> <li>Do not apply before 09:00 and after 16:00 in the winter.</li> <li>Do not apply exterior if it looks like rain will occur with in 4-6 hours of application.</li> </ul>	
<b>Surface Preparation</b>		
• <b>Uncoated cement Plaster surfaces</b>	<ul style="list-style-type: none"> <li>Remove dust, foreign material, fungal and algae growth.</li> <li>Fill all visible cracks</li> </ul>	
• <b>Fibre Cement Surfaces (Uncoated, Weathered or New)</b>	<ul style="list-style-type: none"> <li>Remove dust, foreign material, fungal and algae growth.</li> <li>If friable or powdery, seal with Bonding liquid</li> </ul>	
	<ul style="list-style-type: none"> <li></li> </ul>	
<b>Colour Range and Quantities</b>	<ul style="list-style-type: none"> <li>This Product is available in white</li> <li>Available in 5 and 20litres.</li> </ul>	
<b>Precautions</b>	<ul style="list-style-type: none"> <li>This Product is not flammable, contains no toxic substances and only low levels of VOC (EU regulations).</li> </ul>	
<b>Disclaimer</b>	F4 Paints cannot be held liable if the product fails due to improper surface preparation or application.	